

ELECTRICAL INSULATION AND ASSEMBLY TAPES



We connect your energy

www.cellpack.com



NO. 128

PVC Insulation tape for labelling, bundling and insulation

APPLICATION AREAS

- Sealing
- Padding of cable insulation
- Bundling
- Reinforcing
- As insulation in the electrical and tele-communications sector
- Colour coding

APPLICATION ENVIRONMENT


- Normal/Moderate Temperatures and Conditions

CERTIFICATIONS

- Approved according to VDE
- Type IEC 60454-3-1-5/F-PVCP/90 (except transparent)



ALL PRODUCT INFORMATION



Colours	Length m	Width	Thickness	Art. No. BBC Cellpack
		mm		
Black	10	15	0.15	145821
Blue	10	15	0.15	145825
Yellow	10	15	0.15	145826
Red	10	15	0.15	145827
White	10	15	0.15	145828
Green	10	15	0.15	145829
Violet	10	15	0.15	145830
Grey	10	15	0.15	145831
Brown	10	15	0.15	145832
Orange	10	15	0.15	145822
Green-Yellow	10	15	0.15	145823
Transparent	10	15	0.15	145824
Black	10	19	0.15	145806
Blue	10	19	0.15	145810
Yellow	10	19	0.15	145811
Red	10	19	0.15	145812
White	10	19	0.15	145813
Green	10	19	0.15	145814
Violet	10	19	0.15	145815
Grey	10	19	0.15	145816
Brown	10	19	0.15	145817
Orange	10	19	0.15	145807
Green-Yellow	10	19	0.15	145808

Operating temperature	0 °C up to +90 °C
Thickness	0,15
Adhesive force	1,8 N/cm
Elasticity	170%
Strength (Tensile strength)	30 N/cm
Insulation (Dielectric strength)	40 kV/mm



NO. 328

PVC insulation tape for insulation and bundling

APPLICATION AREAS

- Fixing and protection during cable pull-in
- Bundling and reinforcement
- Sealing
- Marking/labelling of cables or fuses as insulation in the electrical and telecommunications

APPLICATION ENVIRONMENT


- Good workability even at low temperatures

CERTIFICATIONS

- Approval according to VDE
- IEC 60454-3-1-11/F-PVCP/105



ALL
PRODUCT
INFORMATION



Colours	Length m	Width mm	Thickness mm	Art. No. BBC Cellpack
Black	20	12	0.18	416717
Black	20	15	0.18	416721
Black	10	19	0.18	416722
Black	20	19	0.18	416770
Blue	20	19	0.18	416771
Light blue	20	19	0.18	416772
Yellow	20	19	0.18	416773
Red	20	19	0.18	416774
White	20	19	0.18	416775
Green	20	19	0.18	416776
Violet	20	19	0.18	416777
Grey	20	19	0.18	416778
Brown	20	19	0.18	416779
Green-Yellow	20	19	0.18	416780
Mix	20	19	0.18	416781
Black	20	25	0.18	416782
Black	20	30	0.18	416783
Black	20	38	0.18	416784
Grey	20	38	0.18	416785
Black	20	50	0.18	416786
Red	20	50	0.18	416787
White	20	50	0.18	416788
Grey	20	50	0.18	416789

Operating temperature	-18°C up to +105°C
Thickness	0,18
Adhesive force	3 N/cm
Elasticity	300%
Strength (Tensile strength)	35 N/cm
Insulation (Dielectric strength)	45 kV/mm



NO. 388

All-weather PVC tape for insulation and bundling

APPLICATION AREAS

- Sealing
- Padding of cable insulation
- Bundling
- Reinforcing
- As insulation in the electrical and tele-communications sector
- Colour coding
- Resistant to all weather influences

APPLICATION ENVIRONMENT

- Particularly weather-resistant PVC all-weather tape can also be used at low temperatures.

CERTIFICATIONS

- Approved according to VDE
- Type IEC 60454-3-1-5/F-PVCP/90 (except transparent)



ALL
PRODUCT
INFORMATION



Colours	Length m	Width mm	Thickness	Art. No. BBC Cellpack
Black	20	19	0.22	223604
Black	6	19	0.22	223605

Temperatura d'esercizio	-10°C a +90°C
Spessore	0,15
Forza Adesiva	1,8 N/cm
Elasticità	180%
Forza (resistenza alla trazione)	28 N/cm
Isolamento (rigidità dielettrica)	44 kV/mm

Behr Bircher Cellpack BBC Benelux B.V.
 BBC Cellpack Electrical Products
 Keersluisweg 13 | NL 1332 EE Almere Buiten
 +31 36 549 03 36 | info@cellpack.nl

www.cellpack.com