

Art. No.		Typ	Cross section range - Class 5			
previous	new		12 kV	17,5 kV	24 kV	36 kV

Elbow separable connector, for all 1-core polymeric cables, for outer cone system terminals type A						
295167		CWS 250 A 24 kV 16 - 95	50 - 70	50 - 70	50 - 70	
293792		CWS 250 A 24 kV 70 - 150	120	95 - 120	70 - 120	

Straight separable connector, for all 1-core polymeric cables, for outer cone system terminals type A						
295283		CGS 250 A 24 kV 25 - 95	50 - 70	50 - 70	50 - 70	
293797		CGS 250 A 24 kV 70 - 150	120	95 - 120	70 - 120	

Elbow separable connector, for all 1-core polymeric cables, for outer cone system terminals type B						
250720		CWS 400 A 24 kV 25 - 70	50 - 70	50 - 70	50 - 70	
246176		CWS 400 A 24 kV 95 - 240	150 - 185	120 - 185	95 - 185	
250726		CWS 400 A 36 kV 35-95				50 - 70
355826		CWS 400 A 36 kV 120				120
247102		CWS 400 A 36 kV 150-240				150 - 185

T-shaped separable connector, for all 1-core polymeric cables, for outer cone system terminals type C						
250711	355434	CTS 630A 24 kV 25 - 70	50 - 70	50 - 70	50 - 70	
220775	355433	CTS 630A 24 kV 95 - 240	150 - 185	120 - 185	95 - 185	
302732	355561	CTS 630A 24 kV 240 - 300	240 - 300	240 - 300	240 - 300	

250715	355562	CTS 630A 36 kV 35 - 95				50 - 70
256010	355563	CTS 630A 36 kV 95 - 150				95 - 150
224826	355564	CTS 630A 36 kV 150 - 240				150 - 185
256328	356660	CTS 630A 36 kV 240 - 400				240 - 300

T-shaped separable coupling connector, for all 1-core polymeric cables, for separable connector type CTS						
256838		CTKS 630A 24 kV 25 - 70	50 - 70	50 - 70	50 - 70	
256839		CTKS 630A 24 kV 95 - 240	150 - 185	120 - 185	95 - 185	

257581		CTKS 630A 36 kV 35 - 95				50 - 70
257582		CTKS 630A 36 kV 150 - 240				150 - 185